



## C.L-J-040Y

### 调速挂溜式滚桶机

研磨系列

### Metal tumbling machine

Grinding series

#### 功能

被加工金属工件均一光亮，自带调速变频功能，自动报警系统，PLC人性化系统控制。

#### 优点

- 人性化数码控制整机
- 零件脱落自动报警
- 一键式定位开门装置
- 上下挂具筒易式操作

#### 配置

- 台湾刹车马达
- 原装台湾减速机
- 原装进口三星皮带
- 原装日本NSK耐磨轴承
- 英威腾大功率变频器
- PLC人机界面

#### 技术参数 / Technical Parameters

性能指标项 Performance index	标准值 Standard value	竹板厚度 The thickness of bamboo board	25MM
装夹五金件 Number of clamping mirror brackets	1000-2000	工作电压 Working voltage	380V/50HZ
大桶主轴转速 The spindle speed of big tank	0-30转 0-30 rpm	操作系统 Operating system	PLC
挂具转速 Rack speed	5-115转 5-115 rpm	床体重量 Machine tool weight	1250KG
主轴功率 Spindle power	3.5KW	外型尺寸 External dimension	1600*1500*1700

#### Functions

Uniform and bright processed workpieces, speed-regulating frequency conversion, automatic alarm system and PLC humanized control system.

#### Advantages

- Humanized digital control the whole machine
- Automatic alarm for parts falling off
- One-button positioning door opener
- Easy operation with racks at the top and bottom

#### Configuration

- Taiwan brake motor
- Original Taiwan decelerator
- Original imported Samsung belt
- Original Japanese NSK antifriction bearing
- Invt high-power inverter
- PLC man-machine interface